



Propoxyated ethoxylated linear alcohol
Concentration >99 %

Physical and chemical Properties

Polarity:	Nonionic
Density:	1.02 g/cm ³
Boiling point:	200 °C
Viscosity (25 °C):	142 mps
Flash point (Cleveland open cup):	190 °C

Specification

Appearance at 25 °C:	clear to slightly hazy liquid
Colour (Gardner):	max. 3
Water (K. Fischer):	0.5 %
Cloud point at 1%:	25–29 °C

pH = 7 (mg KOH/g):	max. 0.5
--------------------	----------

Packaging

Plastic bottle.
5 or 10 kg net weight.

Application

- Low foaming surfactant for brazing flux suspensions (up to 50 °C)
- Recommended concentration: 0.1 to 0.2 %

Classification

CAS No.: 68603-25-8

Classified as hazardous according to the European regulation (EC) 1272/2008 (GHS)

GHS Labelling:
Signal Word: Danger

Hazard Symbols:
GHS05

Hazard Statements:
H318

Precautionary Statements:
P280,
P305+P351+P338,
P310

Safety recommendations and additional information can be found in the Safety Data Sheet (SDS).

MANAGEMENTSYSTEM



DQS – certified according
DIN EN ISO 9001:2008
ISO/TS 16949:2009
DIN EN ISO 14001:2004
BS OHSAS 18001:2007

ANTAROX is registered trademark of
Solvay Novacare

Solvay Fluor GmbH

Postfach 220 Phone +49 511 857-0
30002 Hannover, Germany Fax +49 511 857-2146

www.nocolok.com

Disclaimer: All statements, information, and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and protection of human welfare and the environment.



SOLVAY

asking more from chemistry®



乙氧基丙氧基化-C8-10-脂肪醇
浓度: > 99 %

物理化学特性

极性: 非离子
密度: 1.02 g/cm³
沸点: 200 °C
粘度 (25°C): 142 mps
闪点
(克利夫兰开口杯): 190 °C

规格

25 °C 时外观:
清澈至略浑浊液体
颜色(加德纳): max. 3
水(费希尔): 0.5 %
浊点(1%时): 25 – 29 °C

pH = 7(mg KOH/g) max. 0.5

包装

塑料瓶
净重 5 和 10 kg

应用

- 用于钎剂悬浮液的低泡表面活性剂 (至 50 °C)
- 推荐浓度:
0.1 – 0.2%

分类信息

CAS 号: 68603-25-8

根据欧洲法规 (EC)
被分类为危险品 1272/2008

GHS 标签:
标记文字: 危险

危害标记:
GHS05

危害声明:
H318

预防声明:
P280,
P305 + P351 + P338,
P310

安全建议及附加信息参照
材料安全数据说明 (SDS)

MANAGEMENTSYSTEM



DQS – certified according
DIN EN ISO 9001:2008
ISO/TS 16949:2009
DIN EN ISO 14001:2004
BS OHSAS 18001:2007

ANTAROX is registered trademark of
Solvay Novacare

Solvay Fluor GmbH

Postfach 220 Phone +49 511 857-0
30002 Hannover, Germany Fax +49 511 857-2146

www.nocolok.com

Disclaimer: All statements, information, and data given herein are believed to be accurate and reliable but are presented without guarantee, warranty or responsibility of any kind, express or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement, and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated, or that other measures may not be required. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and protection of human welfare and the environment.



SOLVAY

asking more from chemistry®