# **NOCOLOK®** Braze Paste X 43-7



# **Physical Properties**

Color: Silver Gray
Solidus: 577 °C (1,070 °F)
Liquidus: 613 °C (1,135 °F)

Density: N/A

Electric

Conductivity (%IACS): N/A

Electric Resistivity
(Michrom-cm): N/A
Tensile Strength: 35,000 psi
Shear Strength: N/A psi

## **Metal Composition**

Silicon: 6.5-7.5 %
Aluminium: Balance
Others Total: 0.15% max

#### Flux:

NOCOLOK® Flux

AWS A5.10 ER 4343 Alloy QQB 655A BalSi-2

## **Packaging**

5 kg HDPE bucket

# **Application**

NOCOLOK® Braze Paste X43-7 is a braze paste specifically formulated for providing viscous mixture of flux and alloy for brazing noncladded aluminium materials, including 1100, 3001 and 6061 series aluminium. It is also used for supplying supplemental alloy where necessary on cladded components.

Paste can be dispensed manually by brush, syringe, or with automatic dispensing equipment.

The paste can be used in both furnace and flame braze process.

CsAlF<sub>4</sub> Flux can be added to accommodate materials with Mg of up to 0.12 %.

## Classification

Classified as hazardous according to the European regulation (EC) 1272/2008 (GHS)

GHS Labelling: Signal Word: Danger

Hazard Symbols: GHS07, GHS08

Hazard Statements: H315, H319, H332, H362, H372, H412

Precautionary Statements: P260, P263, P273, P280, P305+P351+P338, P308+P313, P501

Additional information can be found in the Safety Data Sheet (SDS).

### **MANAGEMENTSYSTEM**





DQS – certified according DIN EN ISO 9001:2008 ISO/TS 16949:2009 DIN EN ISO 14001:2004 BS OHSAS 18001:2007

NOCOLOK is registered trademark of Solvay Fluor GmbH, Germany

## **Solvay Fluor GmbH**

Postfach 220 Phone +49 511 857-0 30002 Hannover, Germany Fax +49 511 857-2146



